

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) An apparatus comprising:  
  
a mixer for mixing a received signal and a local oscillator signal and generating an analog, frequency converted signal, and  
  
an analog-to-digital converter for converting the analog, frequency-converted signal into a corresponding digital signal,  
  
wherein the apparatus is used in a receiver without a filter between the mixer and the analog-to-digital converter, and  
  
wherein a frequency of the local oscillator signal is set in relation to a frequency of a sampling rate of the analog-to-digital converter to avoid aliasing in a desired receive band.
2. (Previously Presented) The apparatus in claim 1, wherein the frequency of the local oscillator signal is an integer multiple of half of the sampling rate of the analog-to-digital converter.
3. (Original) The apparatus in claim 1, wherein the frequency of the local oscillator signal  $F_{LO}$  is  $F_{LO} = n * F_{ADC} / 2$ , where  $F_{ADC}$  is the sampling rate of the analog-to-digital converter, and  $n$  is a positive integer.
4. (Original) The apparatus in claim 1, further comprising:  
  
an oscillator for generating a periodic signal,  
  
wherein the periodic signal is used to generate both the local oscillator signal and a sampling rate signal for the analog-to-digital converter.
5. (Original) The apparatus in claim 4, further comprising:

a frequency changer, receiving the periodic signal from the oscillator, for providing the local oscillator signal to the mixer and a sampling rate signal to the analog-to-digital converter.

6. (Original) The apparatus in claim 5, wherein the frequency changer includes a first frequency divider for dividing the periodic signal in half to generate the local oscillator signal and for dividing the periodic signal by an integer to generate the sampling rate signal of the analog-to-digital converter.

7. (Canceled).

8. (Canceled).

9. (Original) The apparatus in claim 1, wherein the analog, frequency-converted signal from the mixer is coupled directly to the analog-to-digital converter.

10-23. (Canceled).

24. (Previously Presented) An apparatus comprising:

a mixer for mixing a received signal and a local oscillator signal to generate an analog, frequency-converted signal, and

an analog-to-digital converter for converting the analog, frequency-converted signal into a corresponding digital signal,

wherein the apparatus is used in a receiver without a filter between the mixer and the analog-to-digital converter, and

wherein a frequency of the local oscillator signal is related to a sampling rate of the analog-to-digital converter to prevent aliasing that would otherwise result from the mixing and converting.

25. (Original) The apparatus in claim 24, wherein the frequency of the local oscillator signal is an integer multiple of half of the sampling rate of the analog-to-digital converter.

26. (Original) The apparatus in claim 24, wherein the frequency of the local oscillator signal  $F_{LO}$  is  $F_{LO} = n * F_{ADC} / 2$ , where  $F_{ADC}$  is the sampling rate of the analog-to-digital converter, and  $n$  is a positive integer.

27. (Canceled).

28. (Canceled).

29. (Original) The apparatus in claim 24, wherein the analog, frequency-converted signal from the mixer is coupled directly to the analog-to-digital converter.

30. (Previously Presented) A method comprising:

receiving an analog signal;

mixing the received signal and a local oscillator signal to generate an analog, frequency-converted signal, and

converting the analog, frequency-converted signal into a corresponding digital signal using a sampling rate signal without filtering the analog, frequency-converted signal,

wherein a frequency of the local oscillator signal is set in relation to a frequency of a sampling rate of the analog-to-digital converter to avoid aliasing in a desired receive band.

31. (Previously Presented) The method in claim 30, wherein the frequency of the local oscillator signal is an integer multiple of half of the frequency of the sampling rate signal.

32. (Original) The method in claim 30, wherein the frequency of the local oscillator signal  $F_{LO}$  is  $F_{LO} = n * F_{ADC} / 2$ , where  $F_{ADC}$  is the frequency of the sampling signal, and  $n$  is a positive integer.

33. (Original) The method in claim 30, further comprising:

determining a receive frequency band for the received signal and a sampling rate range for the analog to digital conversion;

defining limits for the frequency of the local oscillator signal in accordance with the receive frequency band and the frequency of the sampling signal in accordance with the sampling rate range; and

selecting, within the defined limits, the frequency of the local oscillator signal and the frequency of the sampling rate signal so that the frequency of the local oscillator signal is an integer multiple of half of the frequency of the sampling rate signal.

34. (Canceled).

35. (Previously Presented) The apparatus in claim 1, further comprising:

an antenna;

a front end for processing a radio frequency signal received via the antenna; and

digital processing circuitry for processing the digital signal.

36. (Canceled).

37. (Previously Presented) The apparatus in claim 24, further comprising:

an antenna;

a front end for processing a radio frequency signal received via the antenna; and

digital processing circuitry for processing the digital signal.